



Machine suitable for
adhesive lay down

700.50



State of the art technology for high
output and top quality productions



Macchina per applicare su tessuto una pellicola biadesiva e rifilare il bordo.

La macchina ha le seguenti caratteristiche ed è completa di:

- * ruota di taglio con angolo 0° e diametro 40mm
- * ruota di trasporto superiore gommata diametro 48mm con pressione regolabile
- * ruote di trasporto inferiori gommate diametro 48 mm
- * sonotrodo 28Khz
- * dispositivo per aspirazione ritagli
- * guida nastro calda con programmazione della temperatura e regolabile per le varie larghezze di nastro (con dima di regolazione)
- * dispositivo riscaldamento superiore nastro tramite aria calda con programmazione delle temperature indipendenti
- * Touch Screen da 7" con USB



Machine suitable for adhesive lay down with simultaneous edge fabric trimming by ultrasonic

The machine is featuring the following characteristics and is complete with:

- * 40 mm diameter cutting wheel with 0° angle
- * upper roller, 48mm diameter with adjustable pressure
- * bottom roller, 48mm diameter
- * 28Khz sonotrode
- * vacuum device to remove fabric waste
- * adjustable hot chute device with programmable temperature
- * upper heating system by air blowing with programmable temperature and air pressure
- * 7" Touch Screen TC7 with USB port

